



GRAPHENSTONE

DECLARATION OF PERFORMANCE

According to Annex III to Regulation (EU) no. 305/2011

Nº 17004

November 13th, 2023

1. Unique identification code of the product-type:

Biosphere Premium

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

EN 1504-2:2004

Surface protection system for concrete.

Method: Coating

Use: Moisture control

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Industria Española para el Desarrollo e Investigación 2100, S.A. (IEDISA) Pol. Ind. Poliviso,

C/ Carpinteros, 25, 41520 El Viso del Alcor, Sevilla, España

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Non-relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System (2+) 4



DECLARATION OF PERFORMANCE

According to Annex III to Regulation (EU) no. 305/2011

Nº 17004

November 13th, 2023

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

ALL WORLD CERTIFICATION. Avda Benjamin Franklin, 19, 46980, Paterna, Valencia, Spain.

Notified agency No. 1170. I have performed the factory inspection and inspection of the production of the factory itself, as well as the current supervision, evaluation and rating of production controls of the factory according to system +2 (4) and issues the certificate

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Non-relevant

9. Declared performance

<i>Technical properties</i>	<i>Performance</i>	<i>Normalized technical specifications</i>
Bond strength by pull-off	>0.80 N /mm ²	UNE-EN 1504-2
Water vapor permeability	Clase I	UNE-EN 1504-2
Determination of the permeability to liquid water	w<0.10 kg/m ² ·h ^{0.5}	UNE-EN 1504-2
Fire behaviour	A1	UNE-EN 1504-2

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

