



Colourless anti-saltpetre treatment to clean up walls damaged by saltpetre. It prevents the appearance of white stains caused by the absorption of water by capillarity and the dragging of salts from the wall.

Features

Protects against the effects of saltpetre.
Prevents the appearance of white spots.
Suitable for indoor and outdoor use.
High resistance and durability.
Does not crack.

Technical properties

Specific weight	1.25 ± 0.05 g/cm ³
pH	12.5 ± 1
Viscosity	< 50 U.K.
Composition	EDTA.Na4
Appearance	Yellowish liquid
Finish	Transparent
VOC Content	< 1 g/l

Yield/Coverage

7-8 m²/l

Exact yield depends on type and condition of substrate, as well as tools used. Exact consumption should be determined by making onsite sample.

Pack size

1 l and 5 l.

Storage

Store in original container. Keep tightly sealed in cool, dry place. Do not store in extremes of temperature, avoid direct exposure to sunlight and protect from frost. Unopened, storage stability is 12 months from date of manufacture. Product may thicken without losing its efficacy. Shake well before use.



Substrate preparation

Surfaces with salt dragging due to capillary water absorption.

The substrate must be dry, firm, well adhered, even and free of any impurities that could hinder the perfect bonding of the product.

Clean the substrate with plenty of water to force the precipitation of the encapsulated salts. Leave to dry for at least 24 hours.

- Any organic growth and/or other impurities should be removed by thorough cleaning using specific products for this purpose.
- If the substrate is not well adhered, remove the non-adherent areas by scraping and brushing.

Application Method

Shake the product until homogenised and apply a layer of product.

Drying

At 25 °C (77 °F) and 60% relative humidity: 24 hours.

Ambient conditions

The working temperature (ambient and substrate) must be between +5 °C and +32 °C. Avoid applying with direct sunlight, on overheated substrates or rain forecast.



Tools

Roller, brush or airless.

Clean tools after use with warm water.

Notes

Mineral substrates must be at least 28 days old, cured and dry.

The surfaces to be painted must be resistant to high alkalinity.

In case of rain, let the surface dry at least 24 hours before application.

It is recommended to protect the treated surface from rain until finishing product application.

Avoid contact with aluminum, copper, copper alloys and nickel.

Parts that are not going to be treated should be protected (glassware or carpentry).

Do not mix with other brands to maintain product efficacy.

Complementary products

It is recommended to use the Graphenstone® product range for complementary actions. Please refer to the corresponding Technical Data Sheets.

Usage warnings

None, particularly in situations where normal product application is expected and by people without any specific medical conditions. Alkaline product, protect skin and eyes especially. Do not inhale the product. Keep out of reach of children.

Waste management | Sustainability gesture

According to local legal regulations. The containers are made of polypropylene. Please contribute to the protection of the environment, do not throw waste down the drain and use the nearest recycling point.

Minimize product waste by carefully estimating the amount you will need. Store any unused product for future use according to the "Storage" guidelines.

Safety information

For information regarding safety, physical, ecological and toxicological details please see the latest version of the product's Material Safety Data Sheet.

Technical support

For further information, please contact your local distributor or manufacturer:

technicalsupport@graphenstone.com

The information provided is given in good faith, based on IEdISA's current knowledge and experience of the product, when correctly stored, handled and applied, in normal situations and according to IEdISA's recommendations. The Technical Data Sheet serves for information and advice, but is not legally binding. In particular, it does not exempt the user from test and check the suitability of the product for the desired application and purpose. IEdISA reserves the right to make modifications that improve the product or its application. This edition invalidates previous editions.

Date of update: 07-2023