



Beewax Premium

Version: feb-17

Beewax Premium is a natural beeswax for the protection of lime-based stuccos. It prevents the absorption of water and contaminants, thus not significantly altering the substrate's permeability to gases and water vapours. Also, prevents the depigmentation of intense colours.

PRODUCT DESCRIPTION

Where to apply:

Ideal for the protection of lime-based stuccos. Particularly suitable for protection of intense colours and humid areas such as bathrooms, kitchens, etc.

Features:

Protection of lime-based stuccos.
Does not alter the breathability of substrates.
Prevents the depigmentation of intense colours.
Good workability.
Tough and long-lasting.
Based on natural waxed.
Suitable for interior and exterior.

Technical properties:

Specific weight	0.9 ± 0.05 g/cm ³
pH	9.5 ± 1
Nature	Natural waxed
Appearance	White liquid
Finish	Colourless

Yield:

As an estimate, we consider 30-40 m²/l. The exact consumption must be determined by means of a sample of the job.

Format:

Available in pots of 0.75 l y 4 l. Inquire about other formats.

Storage:

Keep in original pack, closed and in a cool and dry place. Keep from freezing and avoid direct sun expo-

sure. Unopened, it may be conserved for at least 12 months.

APPLICATION INSTRUCTIONS

Conditions of the substrate:

The substrate must be dry, firm, well-adhered and free from any impurities that may hinder the product from setting fully.

Application method:

Apply one coat evenly.

After 2 hours of application, polish with wool mop for shine intensification.

Drying:

In conditions of 25 °C and 60% relative humidity, allow 24 hours for drying.

Environmental conditions:

The work temperature (environment and substrate) must be greater than +5 °C and less than 32 °C. Do not apply in direct sunlight, nor on substrate heated by the sun.

Tools:

Sponge, trowel or glove with short hair.

Tool cleaning:

Clean tools after use with warm water.

Notes:

The indicated times are for environmental conditions of 25 °C and 60% relative humidity.



Do not apply to surfaces in constant contact with water.

In case of rain, let the substrate dry for at least 48 hours before applying.

It is recommended to protect the treated surface from rain for 4 days.

The parts that are not going to be treated must be protected (glass, wood, etc.).

Should there be strict aesthetic requirements, it is recommended to perform prior tests.

Do not apply decorative glazing and/or self-adhesive templates or other kinds of masking, until one week has past.

Do not mix with other products or specific properties may change.

ADDITIONAL INFORMATION

Usage warnings:

None in particular for normal use and people who do not have special pathologies. Alkaline product, protect skin and eyes especially. Apply with good ventilation, do not inhale product. Keep out of reach of children.

Waste management:

According to local legal provisions. The packages are made of recycled polypropylene.

Safety information:

For information regarding safety, physical, ecological and toxicological information see the latest version of the product's Material Safety Data Sheet.

Technical substrate:

For further information, please contact your local distributor or manufacture:

technicalsupport@graphenstone.com.

The information provided is given in good faith, based on current knowledge and IEdiSA's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of IEdiSA. The Technical Specifications sheet is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. IEdiSA reserves the right to modifications that improve the product or its application. This version invalidates previous ones.