



Contak Premium

Version: feb-17

Contak Premium is a adherence bridge for rendering. It ensures adherence of mortar to all types of surfaces, both metallic and non-metallic. Suitable for interiors and exteriors.

PRODUCT DESCRIPTION

Where to apply:

Ideal for improving adherence and providing mechanical bonding to plastering mortar and adhesives on any type of support.

Especially suitable to enable plastering of a smooth surface such as glass, ceramic, metals, wood, cement, etc.

Features:

Improved mortar grip.
Great adhesive capacity.
Quick and easy application.
Breathable.
Tough and long-lasting.
Excellent flexibility. Not cracking.

Components:

Mineral particles, contained in an emulsion of high quality pure acrylic in an aqueous medium.

Yield:

Coverage depends on the final use and type, texture or absorption of the support. As an estimate, we consider 4-5 m²/l. The exact consumption must be determined by means of a sample of the job.

Format:

Available in pots of 1 l, 5 l y 15 l. Inquire about other formats.

Storage:

Keep in original pack, closed and in a cool and dry place. Keep from freezing and avoid direct sun exposure. Unopened, it may be conserved for at least 12 months. The product may thicken without losing its properties; shake/mix well before use.

Technical properties:

Specific weight	1.25 ± 0.05 g/cm ³
pH	9 ± 1
Viscosity	95 ± 5 K. U.
% solids	63 ± 5 %
Appearance	Dense red liquid
Finish	Granular

APPLICATION INSTRUCTIONS

Conditions of the substrate:

The support must be dry, firm, stable and free from any impurities that may hinder the product from setting fully.

Preparation of the substrate:

If the substrate contains impurities, it is recommended to clean it with pressurised water. Should there be colonies of mould, lichens, algae and bacteria, brush with sodium hypochlorite (bleach) and wait at least 48 hours before application.

If the support is loose (sandy, dusty, etc.), brush and consolidate with *Minerseal Premium* diluted 3:1 with water.

If the support has salt deposits, brush and apply *Neutralysal Premium*.

If the substrate contains a high moisture level, apply *StopWater Premium*.

If the support contains pathologies, then it is necessary to resolve the structural problem first



Application method:

Mix well to ensure an even consistency and Apply one coat, adequately spreading the product.

Drying:

In conditions of 25 °C and 60% relative humidity, allow 24 hours for drying.

Environmental conditions:

The work temperature (environment and substrate) must be greater than +5 °C and less than 32 °C. Do not apply in direct sunlight, nor on support heated by the sun.

Tools:

Roller or brush.

Tool cleaning:

Clean tools after use with warm water.

Notes:

The indicated times are for environmental conditions of 25 °C and 60% relative humidity.

The mineral substrate must be at least 28 days old.

The substrates to be painted must be resistant to high alkalinity.

Do not apply to surfaces in constant contact with water.

In case of rain, let the substrate dry for at least 48 hours before applying.

It is recommended to protect the treated surface from rain until application of the rendering.

The parts that are not going to be treated must be protected (glass, wood, etc.).

Do not mix with other products or specific properties may change.

Complementary products:

It is recommended to use the *Graphenstone* product line for complementary actions, according to the required application, repair and/or finish. Please, refer to the relevant technical datasheets.

ADDITIONAL INFORMATION

Usage warnings:

None in particular for normal use and people who do not have special pathologies. Alkaline product, protect skin and eyes especially. Apply with good ventilation, do not inhale product. Keep out of reach of children.

Waste management:

According to local legal provisions. The packages are made of recycled polypropylene.

Safety information:

For information regarding safety, physical, ecological and toxicological information see the latest version of the product's Material Safety Data Sheet.

Technical substrate:

For further information, please contact your local distributor or manufacture: technicalsupport@graphenstone.com.



The information provided is given in good faith, based on current knowledge and IEdiSA's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of IEdiSA. The Technical Specifications sheet is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. IEdiSA reserves the right to modifications that improve the product or its application. This version invalidates previous ones.

